



CPM601-P

One Device for a wide range of assets and testing applications

Rugged Monitoring presents most advanced Partial Discharge Monitor

(Del 180

CPM601-P One Device for a wide range of assets and testing applications and testing applications



Rugged Monitoring presents most advanced Partial Discharge Monitor **CPM601** to perform PD measurements in dual frequency range i.e., in the range of 0.01MHz - 100MHz as well as 200 – 2000 MHz.

With the help of advanced electronics embedded inside CPM601, user can perform PD measurement using various sensors without the need of using external frequency down converters. This presents All-in-One solution to perform PD measurements using Acoustic, Ultrasonic, HFCT, TEV, Coupling Capacitors as well as UHF Sensors on all assets, GIS, Power Transformers, Rotating Machines and Power Cables.

CPM601-P is a Compact and sturdy enclosure with electronics making it portable, easy to carry, while enabling the user to perform PD measurements with less hassle. Monitor can directly transfer the data to PD Connect software installed on laptop else data can be temporarily stored (optional) in the device enabling the user to record PD pulses with higher sampling rate. Thousands of pulses per second can be transferred to the laptop enabling the user to generate fast and reliable Phase Resolved Partial Discharge (PRPD) graphs. PRPD patterns help the user to identify type of PD. CPM601-P and Software are packed with all necessary tools that help to perform effective PD measurements. Integrated variable amplifiers and onboard denoising features help during onsite testing in case of any huge noise.

We at Rugged Monitoring have a dedicated team for application specific customizations for sensors, monitor configuration and software integration to simplify data collection of testing and monitoring applications.

Applications

- Online periodic partial discharge monitoring
- Online PD measurement during HV AC testing (Resonant test set, VLF, OWTS)
- Multiple point PD monitoring
- Cables and their accessories
- Rotating machines
- AIS/GIS switchgear/switchboards
- Power transformers

Features

- Rugged, compact design
- Dual Frequency Ranges; 0.01MHz 100MHz as well as 200 - 2000 MHz
- Compatible with Acoustic, Ultrasonic, HFCT, TEV, Coupling Capacitors as wells as UHF Sensors
- An interactive and comprehensive software PD Connect for reliable PD measurement and analysis
- Gigabit ethernet copper Cat5e communication link between monitor and laptop
- Optional rugged laptop with installed software suite IP65 rated

Benefits

- Rugged sensors, monitor and laptop
- Gigabit ethernet communication between monitor and laptop
- Enhanced noise rejection
- Realtime denoising

• Software packed with useful tools for reliable and interactive PD measurements


CPM601-P

- Robust recording and analytics
- Customizable according to customer specific applications
- Suitable for Online PD measurements

Technical Specifications

| INPUT CHANNELS | Channels | 8 Multiplexed (4x HF and 4x UHF) |
|---------------------------|---|---|
| | Sampling Rate | 250 MS/s |
| | Amplification | up to 50 dB, software selectable |
| | Filtering | Software configurable band pass filters |
| HF CHANNELS | Bandwidth | 0.01 to 100 MHZ |
| | Sensitivity | 1mV to 2000mV |
| UHF CHANNELS | Bandwidth | 200 - 3000 MHz |
| | Sensitivity | -10 to -70 dBm |
| | Dynamic Range | 60 dBm |
| DATA TRANSFER | High Resolution (pulses data on simultaneous channels) | 10,000 pulses per second for 4 simultaneous channels |
| | Low Resolution (pulse amplitude on simultaneous channels) | 50,000 pulses per second for 4 simultaneous channels |
| | Transfer Rate | 400 Mbps (depending on operating system and connection) |
| MEMORY | SSD | up to 1 TB (Optional) |
| COMMUNICATION LINK | Туре | Ethernet Copper |
| | Connector | RJ45 |
| SYNCHRONISATION INPUTS | 2 Inputs, software | Internal |
| | External | selectable |
| IP RATING | IP 65 | |
| TEMPERATURE RATING | Ambient | -30°C - 60°C |
| | Storage | -40°C - 85°C |
| POWER RATING | Input Power | 100- 240Vac, 45W |
| DIMENSIONS | 260mm(L)x310mm(W)x120mm(H) | |
| LAPTOP | Rugged Laptop | (Optional) |
| | | |






4 = 512 GB Memory 5 = 1 TB Memory

Asset Monitoring : Enterprise Architecture

Compatible with Rugged Monitoring Enterprise Solution



One Solution for Advanced Asset Performance Management System

Manage different industrial assets on one platform without human intervention

Features

- Advanced and Exceptional Reporting Technology with automated alerts
- Modern remote monitoring solutions provide valuable insights to Multiple Assets at Multiple Sites on real-time
- Robust asset health monitoring with analysis and recommendations support asset effectiveness in addition to maximizing equipment uptime
- Establish a real time and consistent monitoring by getting the right information into right hands
- An efficient, reliable partial discharge monitoring for all the assets
- A detailed comprehensive DGA Analysis
- Lifetime Consumption details.

Features Specific to PD Monitoring

- Partial Discharge monitoring and Analysis
- PRPD : Phase resolve partial discharge
- Partial Discharge Amplitude and Discharge rate trend analysis
- Partial Discharge Fault localization
- Artificial Intelligence based PD fault Identification

- Built on well-established remote and cloud-based monitoring technology
- **Simple user-friendly interface** providing fast access to all the features and commands
- Quick and easy 1 step configuration setup
- Encompasses a secure access to data and configuration
- Advanced asset algorithms based on standard ones with new ideas
- Systematic fleet management and analysis
- Extended multilingual support to handle product inquires or troubleshoot problems proactively
- Up System Level Reporting
- Industrial IoT
- Realtime PD Alarm system
- Get Alarm notifications for individual bushing parameters over Email, sms and push notificaions
- Analytics on Online, and offline partial discharge test data

Why Customers Choose Us?

RM solution, the trusted monitoring solution for over 10000+ assets across 50+ countries. We are a leading High Value Electrical Asset Monitoring Company integrating fibre optic technology to the assets.



Attention to Detail

It's our attention to the small stuff, scheduling of timelines and keen project management that makes us stand out from the rest.



A plan for Success

Our Customers are well satisfied with the advisory services that we offer to help them with best in class technological performance and a long durable life.



Experts only We bring in our diversified experienced team with over 100+ years of experience in Asset Monitoring



Meeting Deadlines

Work with us, and you'll work with seasoned professionals – vigilant of deadlines, and committed to exceeding client expectations.



Money Matters

We protect you against currency fluctuation with competitive and fair market prices



Rugged Monitoring Services

Rugged Monitoring provides customization of sensors, monitors & software. In addition we offer on-site commissioning services, maintenance contracts and technical support to all customers worldwide.

(i) About Rugged Monitoring

Industry's leading team of asset condition monitoring experts with 100+ years of combined experience committed to delivering customizable solutions for challenging applications. We offer a range of reliable, high performance, customizable sensors and monitoring solutions that are immune to external influence.

Certification



ISO 9001



ISO 14001



ISO 45001/ OHSAS 18000



Llyod's Register



ATEX Certification

Our Presence Across the Globe



Head Office

Canada
1415 Frank-Carrel, Suite
230, Quebec, QC - G1N
4N7, CANADA

S +1-418-767-0111

Asia Pacific | China | India | Middle East and Africa | Europe | North America | Latin America





info@ruggedmonitoring.com

🔅 www.ruggedmonitoring.com

©2024 Rugged Monitoring Company. All rights reserved. Information subject to change without notice. All trademarks are properties of their respective companies, as noted herein.

